



Powered by: Kizzexx Industries Pvt Ltd



VISION

“Be a dominant lubricant oil and grease company with significant national and international presence, Integrated to lubricant and other petroleum-products”

Drive for achieving the above vision.

- R & D Infrastructure for innovative products.
- Superior manufacturing infrastructure.
- Skilled and experienced manpower.
- Manufacture & supply of quality products.

MISSION

To achieve international standards in all aspects of lubricants and greases with focus on customer delight through value of its products and services and responsible environmental performance.

- To maximize creation of wealth, value and satisfaction for all stake holders.
- To obtain leadership in developing, adopting state-of-the-art technology for competitive advantage.
- To cultivate high standard of business ethics and quality and environmental management.
- We aim to work closely with our customers and partners to advance more efficient and sustainable use of energy and natural resources.
- To seek a high standard of performance, containing a strong long-term and growing position in the competitive environment.

CERTIFICATE




Scan this QR code with smartphone to visit our website

Certificate of Registration

This is to certify that the Quality Management System of
KIZZEXX INDUSTRIES PRIVATE LIMITED
PLOT-B, UNIT-8 PAIKEE SUB PLOT NO-51 TO 53, SHIV BHAKTI INDUSTRIES, PALSANA ROAD, PALSANA, SURAT-394315, GUJARAT, INDIA
 has been assessed independently by RQC and found to comply with the requirements of
(Quality Management System)
ISO 9001:2015
 For the following scope:
MANUFACTURER OF LUBRICANT OIL, ENGINE OIL, HYDRAULIC OIL, GEAR OIL, INDUSTRIAL OIL, AUTOMOTIVE GREASE AND AUTO PARTS

Certification Calendar:
 Client Id: 54524
 Certificate No: QG-58947/1225
 Registered on: 31.12.2025
 Issued on: 31.12.2025
 Expires on: 30.12.2028
 1st Surveillance on/before: 30.12.2026
 2nd Surveillance on/before: 30.12.2027


Executive Director
 RADIANCE QUALITY CERTIFICATIONS
Regd. Office - 20-22 Wenlock Rd, Hoxton, London N1 7GH, UK





Regd. off. 20-22 Wenlock Rd, Hoxton, London N1 7GH, UK
 Terms & conditions
 1. Validity of this certificate is subject to the organization implementing its system in accordance with respective management systems standards along with RQC requirements.
 2. This certificate remains the property of radiance quality certifications to whom it must be returned upon request.
 3. Use of logo must be in accordance with the requirement of the UKAS accreditation board (in any) failure to meet the requirement shall be held liable for actions.
 4. This certificate is not final evidence of certification status, status must be verified in writing from info@radiance.co.uk or it can be verified online at http://radiance.co.uk/certified-clients


Government of India
Form GST REG-06
[See Rule 10(1)]
Registration Certificate Registration Number :
24AALCK4162HIZI

1. Legal Name	KIZZEXX INDUSTRIES PRIVATE LIMITED		
2. Trade Name, if any	KIZZEXX INDUSTRIES PRIVATE LIMITED		
3. Additional trade names, if any			
4. Constitution of Business	Private Limited Company		
5. Address of Principal Place of Business	Building No./Flat No.: PLOT-B UNIT-8 PAIKEE SUB PLOT NO-51 TO 53 Name Of Premises/Building: SHIV BHAKTI INDUSTRIES Road/Street: PALSANA ROAD Locality/Sub Locality: PALSANA City/Town/Village: Palsana District: Surat State: Gujarat PIN Code: 394315		
6. Date of Liability			
7. Period of Validity	From	04/01/2025	To Not Applicable
8. Type of Registration	Regular		
9. Particulars of Approving	Centre		

Signature

Name	Ravindra Upadhyay
Designation	Superintendent
Jurisdictional Office	VADODARA
Date of issue of Certificate	05/01/2025

Note: The registration certificate is required to be prominently displayed at all places of business in the State.

This is a system generated digitally signed Registration Certificate issued based on the approval of application granted on 04/01/2025 by the jurisdictional authority.


Government of India
Form GST REG-06
[See Rule 10(1)]
Registration Certificate Registration Number :
24AALCK4162HIZI

1. Legal Name	KIZZEXX INDUSTRIES PRIVATE LIMITED		
2. Trade Name, if any	KIZZEXX INDUSTRIES PRIVATE LIMITED		
3. Additional trade names, if any			
4. Constitution of Business	Private Limited Company		
5. Address of Principal Place of Business	Building No./Flat No.: PLOT-B UNIT-8 PAIKEE SUB PLOT NO-51 TO 53 Name Of Premises/Building: SHIV BHAKTI INDUSTRIES Road/Street: PALSANA ROAD Locality/Sub Locality: PALSANA City/Town/Village: Palsana District: Surat State: Gujarat PIN Code: 394315		
6. Date of Liability			
7. Period of Validity	From	04/01/2025	To Not Applicable
8. Type of Registration	Regular		
9. Particulars of Approving	Centre		

Signature

Name	Ravindra Upadhyay
Designation	Superintendent
Jurisdictional Office	VADODARA
Date of issue of Certificate	05/01/2025

Note: The registration certificate is required to be prominently displayed at all places of business in the State.

This is a system generated digitally signed Registration Certificate issued based on the approval of application granted on 04/01/2025 by the jurisdictional authority.


भारत सरकार
Government of India
सूक्ष्म, लघु एवं मध्यम उद्यम मंत्रालय
Ministry of Micro, Small and Medium Enterprises


सूक्ष्म, लघु एवं मध्यम उद्यम
 MICRO, SMALL & MEDIUM ENTERPRISES

UDYAM REGISTRATION CERTIFICATE

UDYAM REGISTRATION NUMBER: UDYAM-GJ-22-0451862

NAME OF ENTERPRISE: KIZZEXX INDUSTRIES PRIVATE LIMITED

S.No.	Classification Year	Enterprise Type	Classification Date
1	2024-25	Micro	13/01/2025

TYPE OF ENTERPRISE: **MANUFACTURING**

MAJOR ACTIVITY: **MANUFACTURING**

SOCIAL CATEGORY OF ENTREPRENEUR: **GENERAL**

NAME OF UNIT(S):

S.No.	Name of Unit(s)
1	KIZZEXX INDUSTRIES PRIVATE LIMITED

OFFICIAL ADDRESS OF ENTERPRISE:

Flat/Door/Block No.	PLOT NO-2, 51 TO 53	Name of Premises/ Building	SHIV BHAKTI INDUSTRIES
Village/Town	PALSANA	Block	SURAT
Road/Street/Lane	PALSANA	City	SURAT
State	GUJARAT	District	SURAT, Pin 394315
Mobile	9428149023	Email:	kizzexx@dash406.com

DATE OF INCORPORATION / REGISTRATION OF ENTERPRISE: 27/11/2024

DATE OF COMMENCEMENT OF PRODUCTION/BUSINESS: 27/11/2024

S.No.	NIC 2 Digit	NIC 4 Digit	NIC 5 Digit	Activity
1	19 - Manufacture of coke and refined petroleum products	1920 - Manufacture of refined petroleum products	19201 - Production of liquid and gaseous fuels, illuminating oils, lubricating oils or greases or other products from crude petroleum or bituminous minerals	Manufacturing

DATE OF UDYAM REGISTRATION: 13/01/2025

* In case of graduation (upward/reverse) of status of an enterprise, the benefit of the Government Schemes will be availed as per the provisions of Notification No. S.O. 2119(E) dated 26.06.2020 issued by the MoS, MSME.

Disclaimer: This is computer generated statement, no signature required. Printed from <https://udyamregistration.gov.in> & Date of printing: 13/01/2025

For any assistance, you may contact:

1. District Industries Centre: SURAT (GUJARAT)

2. MSME-DFO: AHMEDABAD (GUJARAT)

BE A CHAMPION
 with the Ministry of MSME



Visit : www.msme.gov.in ; www.dcmsme.gov.in ; www.champions.gov.in

Follow us @minmsme & @msmechampions

A motorcyclist in a black racing suit and helmet is riding a black and gold motorcycle on a winding road through a mountainous landscape. The rider is leaning forward, and the motorcycle is in motion, as indicated by the blurred background. The scene is framed by a white border that is slightly tilted. The text "BIKE & MOPED ENGINE OIL" is written in white, bold, sans-serif capital letters at the bottom of the image.

BIKE & MOPED ENGINE OIL

BIKE & MOPED ENGINE OIL

RIDEX 20W40 API SJ/JASO MA



DESCRIPTION

Kizzexx 20W40 API SJ/JASO MA is a high-performance engine oil, especially designed for modern motorcycles. Though developed for latest technology, It provides good protection for old technology engines too, while aligning with motorcycle engine technology development trends.

MEETS OR EXCEEDS

API SJ / JASO MA

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5 °C, gm/CC	ASTM D 4052	0.852
Viscosity @100 °C, cSt	ASTM D 445	14.16
Viscosity @40 °C, cSt	ASTM D 445	110.90
Viscosity Index	ASTM D 2270	120
Pour Point, °C	ASTM D 97	-22
Flash Point, °C	ASTM D 92	231
TBN, mgKOH/gm	ASTM D 892	5.6

PACKAGING SIZE

900ml, 1Ltr, 1.2Ltr, 20Ltr, 55Ltr, 210Ltr

RIDEX 20W40 API SL/JASO MA 2



DESCRIPTION

Kizzexx 20W40 API SL/JASO MA 2 is a high-performance engine oil, especially designed for modern motorcycles. Though developed for latest technology, It provides good protection for old technology engines too, while aligning with motorcycle engine technology development trends.

MEETS OR EXCEEDS

API SL / JASO MA 2

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5 °C, gm/CC	ASTM D 4052	0.865
Viscosity @100 °C, cSt	ASTM D 445	14.27
Viscosity @40 °C, cSt	ASTM D 445	114.88
Viscosity Index	ASTM D 2270	125
Pour Point, °C	ASTM D 97	-27
Flash Point, °C	ASTM D 92	235
TBN, mgKOH/gm	ASTM D 892	6.3

PACKAGING SIZE

900ml, 1Ltr, 1.2Ltr, 20Ltr, 55Ltr, 210Ltr

RIDEX 20W40 API SM/JASO MA 2



DESCRIPTION

Kizzexx 20W40 API SM/JASO MA 2 is a high-performance engine oil, especially designed for modern motorcycles. Though developed for latest technology, It provides good protection for old technology engines too, while aligning with motorcycle engine technology development trends.

MEETS OR EXCEEDS

API SM / JASO MA 2

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5 °C, gm/CC	ASTM D 4052	0.869
Viscosity @100 °C, cSt	ASTM D 445	15.38
Viscosity @40 °C, cSt	ASTM D 445	127.48
Viscosity Index	ASTM D 2270	125
Pour Point, °C	ASTM D 97	-27
Flash Point, °C	ASTM D 92	237
TBN, mgKOH/gm	ASTM D 892	6.5

PACKAGING SIZE

900ml, 1Ltr, 1.2Ltr, 20Ltr, 55Ltr, 210Ltr

RIDEX 20W40 API SN/JASO MA 2



DESCRIPTION

Kizzexx 20W40 API SN/JASO MA 2 is a high-performance engine oil, especially designed for modern motorcycles. Though developed for latest technology, It provides good protection for old technology engines too, while aligning with motorcycle engine technology development trends.

MEETS OR EXCEEDS

API SN / JASO MA 2

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5 °C, gm/CC	ASTM D 4052	0.875
Viscosity @100 °C, cSt	ASTM D 445	16.50
Viscosity @40 °C, cSt	ASTM D 445	140.08
Viscosity Index	ASTM D 2270	126
Pour Point, °C	ASTM D 97	-27
Flash Point, °C	ASTM D 92	241
TBN, mgKOH/gm	ASTM D 892	6.7

PACKAGING SIZE

900ml, 1Ltr, 1.2Ltr, 20Ltr, 55Ltr, 210Ltr

BIKE & MOPED ENGINE OIL

RIDEX 10W30 API SN/JASO MB



DESCRIPTION

Kizzexx 10W-30 API SN /JASO MB is a synthetic bike engine oil enhanced with high quality additives for the latest generation four stroke motorcycles. This high-quality oil helps maintain a cleaner engine and improves efficiency. The low viscosity delivers instant cold starts and enhances fuel efficiency.

MEETS OR EXCEEDS

API SN / JASO MB

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5 °C,gm/CC	ASTM D 4052	0.851
Viscosity @100 °C, cSt	ASTM D 445	10.69
Viscosity @40 °C, cSt	ASTM D 445	66.81
Viscosity Index	ASTM D 2270	149
Pour Point, °C	ASTM D 97	-33
Flash Point, °C	ASTM D 92	238
TBN, mgKOH/gm	ASTM D 892	7.1

PACKAGING SIZE

600ml, 650ml, 800ml, 850ml, 900ml, 1Ltr, 1.2Ltr, 20Ltr, 55Ltr, 210Ltr

RIDEX 10W40 API SN/JASO MB



DESCRIPTION

Kizzexx 10W40 API SN/JASO MB is a synthetic bike engine oil enhanced with high quality additives for the latest generation four stroke motorcycles. This high-quality oil helps maintain a cleaner engine and improves efficiency. The low viscosity delivers instant cold starts and enhances fuel efficiency.

MEETS OR EXCEEDS

API SN / JASO MB

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5 °C,gm/CC	ASTM D 4052	0.860
Viscosity @100 °C, cSt	ASTM D 445	15.50
Viscosity @40 °C, cSt	ASTM D 445	105.95
Viscosity Index	ASTM D 2270	155
Pour Point, °C	ASTM D 97	-33
Flash Point, °C	ASTM D 92	232
TBN, mgKOH/gm	ASTM D 892	7.8

PACKAGING SIZE

800ml, 900ml, 1Ltr, 1.2Ltr, 20Ltr, 55Ltr, 210Ltr

RIDEX 20W50 API SN/JASO MA 2



DESCRIPTION

Kizzexx 20W50 API SN/JASO MA2 is a high-performance engine oil, especially designed for modern motorcycles. Though developed for latest technology, It provides good protection for old technology engines too, while aligning with motorcycle engine technology development trends meets major OEMs.

MEETS OR EXCEEDS

API SN / JASO MA 2

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5 °C,gm/CC	ASTM D 4052	0.880
Viscosity @100 °C, cSt	ASTM D 445	19.50
Viscosity @40 °C, cSt	ASTM D 445	169.27
Viscosity Index	ASTM D 2270	132
Pour Point, °C	ASTM D 97	-24
Flash Point, °C	ASTM D 92	242
TBN, mgKOH/gm	ASTM D 892	7.8

PACKAGING SIZE

900ml, 1Ltr, 1.2Ltr, 20Ltr, 55Ltr, 210Ltr

RIDEX 15W50 API SN/JASO MA 2



DESCRIPTION

Waxity 15W-50 API SN / JASO MA2 is a synthetic blend formulated specifically for new generation higher CC four stroke motorcycles ideal for daily commute or recreational riding. It offers superior wear protection, excellent oxidation resistance, and improved oil film that keeps the engine running efficiently.

MEETS OR EXCEEDS

API SN / JASO MA 2

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5 °C,gm/CC	ASTM D 4052	0.860
Viscosity @100 °C, cSt	ASTM D 445	18.90
Viscosity @40 °C, cSt	ASTM D 445	155.10
Viscosity Index	ASTM D 2270	138
Pour Point, °C	ASTM D 97	-28
Flash Point, °C	ASTM D 92	244
TBN, mgKOH/gm	ASTM D 892	6.2

PACKAGING SIZE

1.7Ltr, 2.5Ltr, 3Ltr, 20Ltr, 55Ltr, 210Ltr

BIKE & MOPED ENGINE OIL

RIDEX 5W30 API SP/ACEA A5/B5



DESCRIPTION

Kizzexx Synthetic Engine Oil SAE 5W30 API SP ACEA A5/B5 is an advanced synthetic motorcycle oil designed to keep your engine running like new by providing exceptional wear protection, cleaning power and 5W30 overall performance. A fuel economy, universal motorcycle oil, developed according to the most recent technology.

MEETS OR EXCEEDS

API SP / ACEA A5/B5

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5°C,gm/CC	ASTM D 4052	0.835
Viscosity @100°C, cSt	ASTM D 445	11.50
Viscosity @40°C, cSt	ASTM D 445	68.20
Viscosity Index	ASTM D 2270	164
Pour Point, °C	ASTM D 97	-39
Flash Point, °C	ASTM D 92	220
TBN, mgKOH/gm	ASTM D 892	7.1

PACKAGING SIZE

600ml, 650ml, 800ml, 1Ltr, 20Ltr, 55Ltr, 210Ltr

RIDEX 2T API TC/JASO FC



DESCRIPTION

Kizzexx 2T API TC/JASO FC is a new generation semi-synthetic, extremely low smoke, environmentally friendly two stroke engine oil. It is blended from highly virgin mineral base oils, special synthetic base fluid and fortified with finely balanced low ash additives. It keeps engine clean and protected.

MEETS OR EXCEEDS

API TC / JASO FC

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5°C,gm/CC	ASTM D 4052	0.847
Viscosity @100°C, cSt	ASTM D 445	7.2
Viscosity @40°C, cSt	ASTM D 445	42.2
Viscosity Index	ASTM D 2270	134
Pour Point, °C	ASTM D 97	-18
Flash Point, °C	ASTM D 92	180
TBN, mgKOH/gm	ASTM D 892	0.0

PACKAGING SIZE

900ml, 1Ltr, 1.2Ltr, 20Ltr, 55Ltr, 210Ltr

ENGINE OIL VISCOSITY CLASSIFICATION (SAE)

Cold 'Winter' Rating



SAE low temperature viscosity measurement at cold temperatures

Thinner → → Thicker

Hot Rating



SAE high temperature viscosity measured at 100°C (Standard Operating Temp)



CAR & LMV ENGINE OIL

CAR & LMV ENGINE OIL

DRIFTEX OW16 API SP



DESCRIPTION

Kizzexx Full Synthetic Engine Oil API SP SAE OW16 is an advanced fully Synthetic motor oil designed to keep your engine running like new by providing exceptional wear protection, cleaning power and overall performance. A fuel economy, universal motor oil, developed according the most recent technology.

MEETS OR EXCEEDS
API SP | ILSAC GF-6B

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5 °C,gm/CC	ASTM D 4052	0.835
Viscosity @100 °C, cSt	ASTM D 445	8.0
Viscosity @40 °C, cSt	ASTM D 445	41.35
Viscosity Index	ASTM D 2270	170
Pour Point, °C	ASTM D 97	-42
Flash Point, °C	ASTM D 92	220
TBN, mgKOH/gm	ASTM D 892	7.1

PACKAGING SIZE

1Ltr, 3 Ltr, 3.5Ltr, 4Ltr, 5Ltr, 6Ltr
7.5Ltr, 20Ltr, 55Ltr, 210Ltr

DRIFTEX OW20 API SP



DESCRIPTION

Kizzexx Full Synthetic Engine Oil API SP SAE OW20 is an advanced fully Synthetic motor oil designed to keep your engine running like new by providing exceptional wear protection, cleaning power and overall performance. A fuel economy, universal motor oil, developed according to the most recent technolog.

MEETS OR EXCEEDS
API SP | ILSAC GF-5

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5 °C,gm/CC	ASTM D 4052	0.835
Viscosity @100 °C, cSt	ASTM D 445	8.0
Viscosity @40 °C, cSt	ASTM D 445	41.35
Viscosity Index	ASTM D 2270	170
Pour Point, °C	ASTM D 97	-42
Flash Point, °C	ASTM D 92	220
TBN, mgKOH/gm	ASTM D 892	7.1

PACKAGING SIZE

1Ltr, 3 Ltr, 3.5Ltr, 4Ltr, 5Ltr, 6Ltr
7.5Ltr, 20Ltr, 55Ltr, 210Ltr

DRIFTEX OW30 API SP



DESCRIPTION

Kizzexx Full Synthetic Engine Oil API SP SAE OW30 is an advanced fully Synthetic motor oil designed to keep your engine running like new by providing exceptional wear protection, cleaning power and overall performance. A fuel economy, universal motor oil, developed according to the most recent technology.

MEETS OR EXCEEDS
API SP | ILSAC GF-6A

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5 °C,gm/CC	ASTM D 4052	0.835
Viscosity @100 °C, cSt	ASTM D 445	11.00
Viscosity @40 °C, cSt	ASTM D 445	61.60
Viscosity Index	ASTM D 2270	173
Pour Point, °C	ASTM D 97	-42
Flash Point, °C	ASTM D 92	220
TBN, mgKOH/gm	ASTM D 892	7.1

PACKAGING SIZE

1Ltr, 3 Ltr, 3.5Ltr, 4Ltr, 5Ltr, 6Ltr
7.5Ltr, 20Ltr, 55Ltr, 210Ltr

DRIFTEX OW40 API SN/CF



DESCRIPTION

Kizzexx Full Synthetic Engine Oil API SN/CF SAE OW40 is an advanced fully Synthetic motor oil designed to keep your engine running like new by providing exceptional wear protection, cleaning power and overall performance. A fuel economy, universal motor oil, developed according to the most recent technology.

MEETS OR EXCEEDS
API SN/CF | ILSAC GF-5

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5 °C,gm/CC	ASTM D 4052	0.835
Viscosity @100 °C, cSt	ASTM D 445	14.50
Viscosity @40 °C, cSt	ASTM D 445	86.55
Viscosity Index	ASTM D 2270	175
Pour Point, °C	ASTM D 97	-42
Flash Point, °C	ASTM D 92	220
TBN, mgKOH/gm	ASTM D 892	7.1

PACKAGING SIZE

1Ltr, 3 Ltr, 3.5Ltr, 4Ltr, 5Ltr, 6Ltr
7.5Ltr, 20Ltr, 55Ltr, 210Ltr

CAR & LMV ENGINE OIL

DRIFTEX 5W20 API SN/CF



DESCRIPTION

Kizzexx Full Synthetic Engine Oil API SN/CF SAE 5W20 is an advanced fully Synthetic motor oil designed to keep your engine running like new by providing exceptional wear protection, cleaning power and overall performance. A fuel economy, universal motor oil, developed according to the most recent technology.

MEETS OR EXCEEDS
API SN/CF | ILSAC GF-5

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5 °C,gm/CC	ASTM D 4052	0.835
Viscosity @100 °C, cSt	ASTM D 445	8.0
Viscosity @40 °C, cSt	ASTM D 445	42.85
Viscosity Index	ASTM D 2270	162
Pour Point, °C	ASTM D 97	-39
Flash Point, °C	ASTM D 92	220
TBN, mgKOH/gm	ASTM D 892	7.1

PACKAGING SIZE

1Ltr, 3 Ltr, 3.5Ltr, 4Ltr, 5Ltr, 6Ltr
7.5Ltr, 20Ltr, 55Ltr, 210Ltr

DRIFTEX 5W30 API SN/CF



DESCRIPTION

Kizzexx Full Synthetic Engine Oil API SN/CF SAE 5W30 is an advanced fully Synthetic motor oil designed to keep your engine running like new by providing exceptional wear protection, cleaning power and overall performance. A fuel economy, universal motor oil, developed according to the most recent technology.

MEETS OR EXCEEDS
API SN/CF | ACEA A5/B5

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5 °C,gm/CC	ASTM D 4052	0.835
Viscosity @100 °C, cSt	ASTM D 445	11.50
Viscosity @40 °C, cSt	ASTM D 445	68.20
Viscosity Index	ASTM D 2270	164
Pour Point, °C	ASTM D 97	-39
Flash Point, °C	ASTM D 92	220
TBN, mgKOH/gm	ASTM D 892	7.1

PACKAGING SIZE

1Ltr, 3 Ltr, 3.5Ltr, 4Ltr, 5Ltr, 6Ltr
7.5Ltr, 20Ltr, 55Ltr, 210Ltr

DRIFTEX 5W40 API SN/CF



DESCRIPTION

Kizzexx Full Synthetic Engine Oil API SN/CF SAE 5W40 is an advanced fully Synthetic motor oil designed to keep your engine running like new by providing exceptional wear protection, cleaning power and overall performance. A fuel economy, universal motor oil, developed according to the most recent technology.

MEETS OR EXCEEDS
API SN/CF | ACEA A3/B4

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5 °C,gm/CC	ASTM D 4052	0.835
Viscosity @100 °C, cSt	ASTM D 445	15.20
Viscosity @40 °C, cSt	ASTM D 445	95.65
Viscosity Index	ASTM D 2270	168
Pour Point, °C	ASTM D 97	-39
Flash Point, °C	ASTM D 92	220
TBN, mgKOH/gm	ASTM D 892	7.1

PACKAGING SIZE

1Ltr, 3 Ltr, 3.5Ltr, 4Ltr, 5Ltr, 6Ltr
7.5Ltr, 20Ltr, 55Ltr, 210Ltr

DRIFTEX 10W30 API CI-4/SL



DESCRIPTION

Kizzexx Full Synthetic Engine Oil API CI 4 SL SAE 10W30 is an advanced fully Synthetic motor oil designed to keep your engine running like new by providing exceptional wear protection, cleaning power and overall performance. A fuel economy, universal motor oil, developed according to the most recent technology.

MEETS OR EXCEEDS
API CI-4/SL | ACEA A3/B4

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5 °C,gm/CC	ASTM D 4052	0.860
Viscosity @100 °C, cSt	ASTM D 445	11.50
Viscosity @40 °C, cSt	ASTM D 445	72.70
Viscosity Index	ASTM D 2270	152
Pour Point, °C	ASTM D 97	-33
Flash Point, °C	ASTM D 92	232
TBN, mgKOH/gm	ASTM D 892	7.1

PACKAGING SIZE

1Ltr, 3 Ltr, 3.5Ltr, 4Ltr, 5Ltr, 6Ltr
7.5Ltr, 20Ltr, 55Ltr, 210Ltr

CAR & LMV ENGINE OIL

DRIFTX 10W40 API SN/CF



DESCRIPTION

Kizzexx Full Synthetic Engine Oil API SN/CF SAE 10W40 is an advanced fully Synthetic motor oil designed to keep your engine running like new by providing exceptional wear protection, cleaning power and overall performance. A fuel economy, universal motor oil, developed according to the most recent technology.

MEETS OR EXCEEDS
API SN/CF

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5 °C,gm/CC	ASTM D 4052	0.860
Viscosity @100 °C, cSt	ASTM D 445	15.50
Viscosity @40 °C, cSt	ASTM D 445	105.95
Viscosity Index	ASTM D 2270	155
Pour Point, °C	ASTM D 97	-33
Flash Point, °C	ASTM D 92	232
TBN, mgKOH/gm	ASTM D 892	7.1

PACKAGING SIZE

1Ltr, 3 Ltr, 3.5Ltr, 4Ltr, 5Ltr, 6Ltr
7.5Ltr, 20Ltr, 55Ltr, 210Ltr

DRIFTX SYN 5W30 API SP



DESCRIPTION

Kizzexx Full Synthetic Engine Oil API SP SAE 5W30 is an advanced fully Synthetic motor oil designed to keep your engine running like new by providing exceptional wear protection, cleaning power and overall performance. A fuel economy, universal motor oil, developed according to the most recent technology.

MEETS OR EXCEEDS
API SP | ILSAC GF-6A

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5 °C,gm/CC	ASTM D 4052	0.835
Viscosity @100 °C, cSt	ASTM D 445	11.50
Viscosity @40 °C, cSt	ASTM D 445	68.20
Viscosity Index	ASTM D 2270	164
Pour Point, °C	ASTM D 97	-39
Flash Point, °C	ASTM D 92	220
TBN, mgKOH/gm	ASTM D 892	7.1

PACKAGING SIZE

1Ltr, 3 Ltr, 3.5Ltr, 4Ltr, 5Ltr, 6Ltr
7.5Ltr, 20Ltr, 55Ltr, 210Ltr

DRIFTX SYN 5W40 API SP



DESCRIPTION

Kizzexx Full Synthetic Engine Oil API SP SAE 5W40 is an advanced fully Synthetic motor oil designed to keep your engine running like new by providing exceptional wear protection, cleaning power and overall performance. A fuel economy, universal motor oil, developed according to the most recent technology.

MEETS OR EXCEEDS
API SP | ILSAC GF-6A

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5 °C,gm/CC	ASTM D 4052	0.835
Viscosity @100 °C, cSt	ASTM D 445	15.20
Viscosity @40 °C, cSt	ASTM D 445	95.65
Viscosity Index	ASTM D 2270	168
Pour Point, °C	ASTM D 97	-39
Flash Point, °C	ASTM D 92	220
TBN, mgKOH/gm	ASTM D 892	7.1

PACKAGING SIZE

1Ltr, 3 Ltr, 3.5Ltr, 4Ltr, 5Ltr, 6Ltr
7.5Ltr, 20Ltr, 55Ltr, 210Ltr

DRIFTX 15W40 API SL/CF



DESCRIPTION

Kizzexx High Performance Technology Engine Oil API SL/CF SAE 15W40 is an advanced motor oil designed to keep your engine running like new by providing exceptional wear protection, cleaning power and overall performance. A fuel economy, universal motor oil, developed according to the most recent technology.

MEETS OR EXCEEDS
API SL/CF | ACEA A3/B3

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5 °C,gm/CC	ASTM D 4052	0.870
Viscosity @100 °C, cSt	ASTM D 445	15.50
Viscosity @40 °C, cSt	ASTM D 445	115.00
Viscosity Index	ASTM D 2270	142
Pour Point, °C	ASTM D 97	-27
Flash Point, °C	ASTM D 92	236
TBN, mgKOH/gm	ASTM D 892	7.2

PACKAGING SIZE

1Ltr, 3 Ltr, 3.5Ltr, 4Ltr, 5Ltr, 6Ltr
7.5Ltr, 20Ltr, 55Ltr, 210Ltr

CAR & LMV ENGINE OIL

DRIFTEX 20W50 API SL/CF



DESCRIPTION

Kizzexx High Performance Technology Engine Oil API SL/CF SAE 20W50 is an advanced motor oil designed to keep your engine running like new by providing exceptional wear protection, cleaning power and overall performance. A fuel economy, universal motor oil, developed according to the most recent technology.

MEETS OR EXCEEDS
API SL/CF

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5°C,gm/CC	ASTM D 4052	0.880
Viscosity @100°C, cSt	ASTM D 445	19.50
Viscosity @40°C, cSt	ASTM D 445	169.27
Viscosity Index	ASTM D 2270	132
Pour Point, °C	ASTM D 97	-24
Flash Point, °C	ASTM D 92	242
TBN, mgKOH/gm	ASTM D 892	7.2

PACKAGING SIZE

1Ltr, 3 Ltr, 3.5Ltr, 4Ltr, 5Ltr, 6Ltr
7.5Ltr, 20Ltr, 55Ltr, 210Ltr

DRIFTEX 20W60 API SL/CF



DESCRIPTION

Kizzexx High Performance Technology Engine Oil API SL/CF SAE 20W60 is an advanced motor oil designed to keep your engine running like new by providing exceptional wear protection, cleaning power and overall performance. A fuel economy, universal motor oil, developed according to the most recent technology.

MEETS OR EXCEEDS
API SL/CF | ACEA A3/B3

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5°C,gm/CC	ASTM D 4052	0.880
Viscosity @100°C, cSt	ASTM D 445	24.50
Viscosity @40°C, cSt	ASTM D 445	223
Viscosity Index	ASTM D 2270	138
Pour Point, °C	ASTM D 97	-24
Flash Point, °C	ASTM D 92	242
TBN, mgKOH/gm	ASTM D 892	7.2

PACKAGING SIZE

1Ltr, 3 Ltr, 3.5Ltr, 4Ltr, 5Ltr, 6Ltr
7.5Ltr, 20Ltr, 55Ltr, 210Ltr

DRIFTEX 25W60 API SL/CF



DESCRIPTION

Kizzexx High Performance Technology Engine Oil API SL/CF SAE 25W60 is an advanced motor oil designed to keep your engine running like new by providing exceptional wear protection, cleaning power and overall performance. A fuel economy, universal motor oil, developed according to the most recent technology.

MEETS OR EXCEEDS
API SL/CF | ACEA A3/B3

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5°C,gm/CC	ASTM D 4052	0.880
Viscosity @100°C, cSt	ASTM D 445	24.50
Viscosity @40°C, cSt	ASTM D 445	223
Viscosity Index	ASTM D 2270	138
Pour Point, °C	ASTM D 97	-24
Flash Point, °C	ASTM D 92	248
TBN, mgKOH/gm	ASTM D 892	7.2

PACKAGING SIZE

1Ltr, 3 Ltr, 3.5Ltr, 4Ltr, 5Ltr, 6Ltr
7.5Ltr, 20Ltr, 55Ltr, 210Ltr




**SAVE MONEY &
NEEDS FEWER REPAIRS**



**QUIETER, COOLER,
SMOOTHER RUNNING
EQUIPMENT**



**USES LESS FUEL &
REDUCES FRICTION**



**INCREASES EFFICIENCY
AND HORSEPOWER**



**LOW OIL
CONSUMPTION**

20FT CONTAINER LOAD UP TO 28 TON MAX



PRODUCT SIZE

UNIT

WEIGHT

QUANTITY

TOTAL WEIGHT

500ML CTN	25	13.86 KG	1144 CTN	15856 KG
1L CTN	20	19.70 KG	882 CTN	17375 KG
1L CTN	12	11.75 KG	1530 CTN	17978 KG
3L CTN	6	18.24 KG	637 CTN	11616 KG
3.5L CTN	6	20.09 KG	637 CTN	12794 KG
5L CTN	4	19.5 KG	576 CTN	11232 KG
7.5L PAIL	1	6.95 KG	1944 PAIL	13501 KG
10L PAIL	1	9.66 KG	1344 PAIL	12983 KG
20L PAIL	1	18.38 KG	756 PAIL	13892 KG
20L DRUM	1	18.90 KG	1242 DRUM	23474 KG
26L DRUM	1	23.14 KG	640 DRUM	14810 KG
50L DRUM	1	47.10 KG	280 DRUM	13160 KG
55L DRUM	1	51.50 KG	280 DRUM	14420 KG
208L BARREL	1	202 KG	80 BARREL	16160 KG
210L BARREL	1	203 KG	80 BARREL	16240 KG

A dark grey Mercedes-Benz truck with a trailer is driving on a road towards the viewer. The scene is set at sunset, with a warm orange and yellow sky and a dark horizon. The truck's headlights are on, and the overall image has a cinematic, high-contrast feel. The truck is positioned in the center of the frame, moving along a road that recedes into the distance. The background shows a desert landscape with some low-lying vegetation and distant mountains under a dramatic sky with scattered clouds.

HEAVY DUTY ENGINE OIL

HEAVY DUTY ENGINE OIL

DEFENDEX 15W40 API CF-4/SJ



DESCRIPTION

Kizzexx Heavy Duty Diesel Engine Oil API CF-4/SJ SAE 15W40 is an advanced Heavy Duty Diesel motor oil designed to keep your engine running like new by providing exceptional wear protection, cleaning power and overall performance. A fuel economy, universal motor oil, developed according to the most recent technology.

MEETS OR EXCEEDS

API CF-4/SJ

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5 °C,gm/CC	ASTM D 4052	0.867
Viscosity @100 °C, cSt	ASTM D 445	14.40
Viscosity @40 °C, cSt	ASTM D 445	107.50
Viscosity Index	ASTM D 2270	137
Pour Point, °C	ASTM D 97	-25
Flash Point, °C	ASTM D 92	230
TBN, mgKOH/gm	ASTM D 892	9.5

PACKAGING SIZE

500ml, 1Ltr, 1.2Ltr, 3 Ltr, 3.5Ltr, 4Ltr, 5Ltr, 6Ltr, 7.5Ltr, 10Ltr, 20Ltr, 55Ltr, 210Ltr

DEFENDEX 15W40 API CH-4/SJ



DESCRIPTION

Kizzexx Heavy Duty Diesel Engine Oil API CH-4/SJ SAE 15W40 is an advanced Heavy Duty Diesel motor oil designed to keep your engine running like new by providing exceptional wear protection, cleaning power and overall performance. A fuel economy, universal motor oil, developed according to the most recent technology.

MEETS OR EXCEEDS

API CH-4/SJ

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5 °C,gm/CC	ASTM D 4052	0.870
Viscosity @100 °C, cSt	ASTM D 445	15.50
Viscosity @40 °C, cSt	ASTM D 445	115
Viscosity Index	ASTM D 2270	142
Pour Point, °C	ASTM D 97	-27
Flash Point, °C	ASTM D 92	235
TBN, mgKOH/gm	ASTM D 892	9.8

PACKAGING SIZE

500ml, 1Ltr, 1.2Ltr, 3 Ltr, 3.5Ltr, 4Ltr, 5Ltr, 6Ltr, 7.5Ltr, 10Ltr, 20Ltr, 55Ltr, 210Ltr

DEFENDEX 15W40 API CI-4+/SL



DESCRIPTION

Kizzexx Heavy Duty Diesel Engine Oil API CI-4+/SL SAE 15W40 is an advanced Heavy Duty Diesel motor oil designed to keep your engine running like new by providing exceptional wear protection, cleaning power and overall performance. A fuel economy, universal motor oil, developed according to the most recent technology.

MEETS OR EXCEEDS

API CI-4+/SL

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5 °C,gm/CC	ASTM D 4052	0.875
Viscosity @100 °C, cSt	ASTM D 445	15.60
Viscosity @40 °C, cSt	ASTM D 445	116
Viscosity Index	ASTM D 2270	142
Pour Point, °C	ASTM D 97	-27
Flash Point, °C	ASTM D 92	235
TBN, mgKOH/gm	ASTM D 892	11.0

PACKAGING SIZE

500ml, 1Ltr, 1.2Ltr, 3 Ltr, 3.5Ltr, 4Ltr, 5Ltr, 6Ltr, 7.5Ltr, 10Ltr, 20Ltr, 55Ltr, 210Ltr

DEFENDEX 15W40 API CK-4/SN



DESCRIPTION

Kizzexx Heavy Duty Synthetic Diesel Engine Oil API CK-4/SN SAE 15W40 is an advanced motor oil designed to keep your engine running like new by providing exceptional wear protection, cleaning power and overall performance. A fuel economy, universal motor oil, developed according to the most recent technology.

MEETS OR EXCEEDS

API CK-4/SN

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5 °C,gm/CC	ASTM D 4052	0.870
Viscosity @100 °C, cSt	ASTM D 445	15.50
Viscosity @40 °C, cSt	ASTM D 445	115.00
Viscosity Index	ASTM D 2270	142
Pour Point, °C	ASTM D 97	-27
Flash Point, °C	ASTM D 92	236
TBN, mgKOH/gm	ASTM D 892	9.6

PACKAGING SIZE

500ml, 1Ltr, 1.2Ltr, 3 Ltr, 3.5Ltr, 4Ltr, 5Ltr, 6Ltr, 7.5Ltr, 10Ltr, 20Ltr, 55Ltr, 210Ltr

HEAVY DUTY ENGINE OIL

DEFENDEX 20W40 API CH/SF



DESCRIPTION

Kizzexx high performance multi grade diesel engine Oil API CH/SF SAE 20W40 is an advanced motor oil designed to keep your engine running like new by providing exceptional wear protection, cleaning power and overall performance. A fuel economy, universal motor oil, developed according to the most recent technology.

MEETS OR EXCEEDS
API CH/SF

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5°C,gm/CC	ASTM D 4052	0.881
Viscosity @100°C, cSt	ASTM D 445	14.50
Viscosity @40°C, cSt	ASTM D 445	126.40
Viscosity Index	ASTM D 2270	115
Pour Point, °C	ASTM D 97	-24
Flash Point, °C	ASTM D 92	236
TBN, mgKOH/gm	ASTM D 892	7.2

PACKAGING SIZE

500ml, 1Ltr, 1.2Ltr, 3 Ltr, 3.5Ltr, 4Ltr, 5Ltr, 6Ltr, 7.5Ltr, 10Ltr, 20Ltr, 55Ltr, 210Ltr

DEFENDEX 20W50 API SL/CF



DESCRIPTION

Kizzexx High Performance Technology Engine Oil API SL/CF SAE 20W50 is an advanced motor oil designed to keep your engine running like new by providing exceptional wear protection, cleaning power and overall performance. A fuel economy, universal motor oil, developed according to the most recent technology.

MEETS OR EXCEEDS
API SL/CF

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5°C,gm/CC	ASTM D 4052	0.880
Viscosity @100°C, cSt	ASTM D 445	19.50
Viscosity @40°C, cSt	ASTM D 445	169.27
Viscosity Index	ASTM D 2270	132
Pour Point, °C	ASTM D 97	-24
Flash Point, °C	ASTM D 92	242
TBN, mgKOH/gm	ASTM D 892	7.2

PACKAGING SIZE

500ml, 1Ltr, 1.2Ltr, 3 Ltr, 3.5Ltr, 4Ltr, 5Ltr, 6Ltr, 7.5Ltr, 10Ltr, 20Ltr, 55Ltr, 210Ltr

DEFENDEX 20W60 API CI-4+/SL



DESCRIPTION

Kizzexx Heavy Duty Diesel Engine Oil API CI-4+/SL SAE 20W60 is an advanced Heavy Duty Diesel motor oil designed to keep your engine running like new by providing exceptional wear protection, cleaning power and overall performance. A fuel economy, universal motor oil, developed according to the most recent technology.

MEETS OR EXCEEDS
API CI-4+/SL

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5°C,gm/CC	ASTM D 4052	0.880
Viscosity @100°C, cSt	ASTM D 445	24.90
Viscosity @40°C, cSt	ASTM D 445	231.75
Viscosity Index	ASTM D 2270	136
Pour Point, °C	ASTM D 97	-24
Flash Point, °C	ASTM D 92	248
TBN, mgKOH/gm	ASTM D 892	11.0

PACKAGING SIZE

500ml, 1Ltr, 1.2Ltr, 3 Ltr, 3.5Ltr, 4Ltr, 5Ltr, 6Ltr, 7.5Ltr, 10Ltr, 20Ltr, 55Ltr, 210Ltr

DEFENDEX 25W60 API CI-4/SL



DESCRIPTION

Kizzexx Heavy Duty Diesel Engine Oil API CI-4/SL SAE 25W60 is an advanced Heavy Duty Diesel motor oil designed to keep your engine running like new by providing exceptional wear protection, cleaning power and overall performance. A fuel economy, universal motor oil, developed according to the most recent technology.

MEETS OR EXCEEDS
API CI-4/SL

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5°C,gm/CC	ASTM D 4052	0.882
Viscosity @100°C, cSt	ASTM D 445	25.0
Viscosity @40°C, cSt	ASTM D 445	234.90
Viscosity Index	ASTM D 2270	135
Pour Point, °C	ASTM D 97	-24
Flash Point, °C	ASTM D 92	248
TBN, mgKOH/gm	ASTM D 892	11.0

PACKAGING SIZE

500ml, 1Ltr, 1.2Ltr, 3 Ltr, 3.5Ltr, 4Ltr, 5Ltr, 6Ltr, 7.5Ltr, 10Ltr, 20Ltr, 55Ltr, 210Ltr

HEAVY DUTY ENGINE OIL

DEFENDEX SAE-40 API CF/SF



DESCRIPTION

Kizzexx Super Premium Engine Oil API CF/SF SAE 40 is an advanced Super Premium motor oil designed to keep your engine running like new by providing exceptional wear protection, cleaning power and overall performance. A fuel economy, universal motor oil, developed according to the most recent technology.

MEETS OR EXCEEDS
API CF/SF

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5°C,gm/CC	ASTM D 4052	0.882
Viscosity @100°C, cSt	ASTM D 445	15.50
Viscosity @40°C, cSt	ASTM D 445	139.25
Viscosity Index	ASTM D 2270	115
Pour Point, °C	ASTM D 97	-18
Flash Point, °C	ASTM D 92	250
TBN, mgKOH/gm	ASTM D 892	8.0

PACKAGING SIZE

500ml, 1Ltr, 1.2Ltr, 3 Ltr, 3.5Ltr, 4Ltr, 5Ltr, 6Ltr, 7.5Ltr, 10Ltr, 20Ltr, 55Ltr, 210Ltr

DEFENDEX SAE-50 API CF/SF



DESCRIPTION

Kizzexx Super Premium Engine Oil API CF/SF SAE 50 is an advanced Super Premium motor oil designed to keep your engine running like new by providing exceptional wear protection, cleaning power and overall performance. A fuel economy, universal motor oil, developed according to the most recent technology.

MEETS OR EXCEEDS
API CF/SF

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5°C,gm/CC	ASTM D 4052	0.883
Viscosity @100°C, cSt	ASTM D 445	20.50
Viscosity @40°C, cSt	ASTM D 445	203.50
Viscosity Index	ASTM D 2270	118
Pour Point, °C	ASTM D 97	-18
Flash Point, °C	ASTM D 92	254
TBN, mgKOH/gm	ASTM D 892	8.0

PACKAGING SIZE

500ml, 1Ltr, 1.2Ltr, 3 Ltr, 3.5Ltr, 4Ltr, 5Ltr, 6Ltr, 7.5Ltr, 10Ltr, 20Ltr, 55Ltr, 210Ltr

DEFENDEX HD-50 API CF/SF



DESCRIPTION

Kizzexx Super Premium Engine Oil API CF/SF HD-50 is an advanced Super Premium motor oil designed to keep your engine running like new by providing exceptional wear protection, cleaning power and overall performance. A fuel economy, universal motor oil, developed according to the most recent technology.

MEETS OR EXCEEDS
API CF/SF

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5°C,gm/CC	ASTM D 4052	0.884
Viscosity @100°C, cSt	ASTM D 445	20.20
Viscosity @40°C, cSt	ASTM D 445	234.0
Viscosity Index	ASTM D 2270	98
Pour Point, °C	ASTM D 97	-18
Flash Point, °C	ASTM D 92	245
TBN, mgKOH/gm	ASTM D 892	8.0

PACKAGING SIZE

500ml, 1Ltr, 1.2Ltr, 3 Ltr, 3.5Ltr, 4Ltr, 5Ltr, 6Ltr, 7.5Ltr, 10Ltr, 20Ltr, 55Ltr, 210Ltr

PERFORMANCE THAT LASTS, MILE AFTER MILE.



**SPECIAL
FORMULATION**



**360° ENGINE
DEFENCE**



**ULTIMATE
PERFORMANCE**



**SMOOTH
SHIFT**

A red John Deere tractor is shown from a front-three-quarter perspective, plowing a field. The tractor is moving from left to right, turning over dark, rich soil. The sky is filled with dramatic, golden-hued clouds, suggesting a sunset or sunrise. The tractor's headlights are on, and its large, treaded tires are prominent. The entire scene is framed by a white border that is slightly tilted.

AGRI + 3 WHEELER ENGINE OIL

AGRICULTURE & 3-WHEELER ENGINE OIL

FARMEX 20W40 API CH



DESCRIPTION

Kizzexx High Performance Multi Grade Tractor Engine Oil API CH SAE 20W40 is an advanced tractor oil designed to keep your engine running like new by providing exceptional wear protection, cleaning power and overall performance. A fuel economy, universal tractor oil, developed according to the most recent technology.

MEETS OR EXCEEDS
API CH

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5 °C, gm/CC	ASTM D 4052	0.878
Viscosity @100 °C, cSt	ASTM D 445	15.18
Viscosity @40 °C, cSt	ASTM D 445	107.16
Viscosity Index	ASTM D 2270	148
Pour Point, °C	ASTM D 97	-30
Flash Point, °C	ASTM D 92	242
TBN, mgKOH/gm	ASTM D 892	7.8

PACKAGING SIZE

500ml, 1Ltr, 3 Ltr, 3.5Ltr, 4Ltr, 5Ltr
6Ltr, 7.5Ltr, 10Ltr, 20Ltr, 55Ltr, 210Ltr

FARMEX UTTO 10W API GL-4



DESCRIPTION

Kizzexx UTTO is a highly developed multi-purpose oil (UTTO - Universal Tractor Transmission Oil) which has been specially formulated for forestry and agricultural machinery. This product meets the requirements of today's combined drive systems (transmission and hydraulic) and wet brakes.

MEETS OR EXCEEDS
API GL-4

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5 °C, gm/CC	ASTM D 4052	0.879
Viscosity @100 °C, cSt	ASTM D 445	11.80
Viscosity @40 °C, cSt	ASTM D 445	74.10
Viscosity Index	ASTM D 2270	154
Pour Point, °C	ASTM D 97	-33
Flash Point, °C	ASTM D 92	222
TBN, mgKOH/gm	ASTM D 892	0.0

PACKAGING SIZE

500ml, 1Ltr, 3 Ltr, 3.5Ltr, 4Ltr, 5Ltr
6Ltr, 7.5Ltr, 10Ltr, 20Ltr, 55Ltr, 210Ltr

AUTO-X X-2T API TC/JASO FC



DESCRIPTION

Kizzexx 2T API TC/JASO FC is a new generation semi-synthetic, extremely low smoke, environmentally friendly two stroke engine oil. It is blended from highly virgin mineral base oils, special synthetic base fluid and fortified with finely balanced low ash additives. It keeps engine clean and protected.

MEETS OR EXCEEDS
API TC/JASO FC

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5 °C, gm/CC	ASTM D 4052	0.847
Viscosity @100 °C, cSt	ASTM D 445	7.2
Viscosity @40 °C, cSt	ASTM D 445	42.2
Viscosity Index	ASTM D 2270	134
Pour Point, °C	ASTM D 97	-18
Flash Point, °C	ASTM D 92	160
TBN, mgKOH/gm	ASTM D 892	0.0

PACKAGING SIZE

500ml, 1Ltr, 20Ltr, 55Ltr, 210Ltr

FARMEX PUMPSET OIL SAE-40 API CC



DESCRIPTION

Kizzexx pumpset oil SAE 40 API CC is a high performance lubricant specifically formulated for diesel engine pump sets used in agricultural, industrial and stationary applications. It combines advanced base oil with premium additives to reduce engine deposits, prevent corrosion, and lower maintenance costs.

MEETS OR EXCEEDS
API CC

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5 °C, gm/CC	ASTM D 4052	0.852
Viscosity @100 °C, cSt	ASTM D 445	13.90
Viscosity @40 °C, cSt	ASTM D 445	105.13
Viscosity Index	ASTM D 2270	112
Pour Point, °C	ASTM D 97	-18
Flash Point, °C	ASTM D 92	233
TBN, mgKOH/gm	ASTM D 892	5.6

PACKAGING SIZE

1Ltr, 3 Ltr, 3.5Ltr, 5Ltr, 10Ltr
20Ltr, 55Ltr, 210Ltr



**AUTOMOTIVE GEAR &
TRANSMISSION OIL**

AUTOMOTIVE GEAR & TRANSMISSION OIL

GEAREX EP-90 API GL-5



DESCRIPTION

Kizzexx Gear Oil SAE 90 API GL-5 are mixed with great mineral base oil, as well as some anti-wear and against froth added substance which has solid oxidation and frothing obstruction use in uncompromising activities tracked down in business armadas, manual transmission, axels and last drives.

MEETS OR EXCEEDS

API GL-5

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5 °C,gm/CC	ASTM D 4052	0.885
Viscosity @100 °C, cSt	ASTM D 445	17.0
Viscosity @40 °C, cSt	ASTM D 445	178
Viscosity Index	ASTM D 2270	101
Pour Point, °C	ASTM D 97	-12
Flash Point, °C	ASTM D 92	240
TBN, mgKOH/gm	ASTM D 892	0.0

PACKAGING SIZE

500ml, 1Ltr, 5Ltr, 10Ltr, 20Ltr
26Ltr, 55Ltr, 210Ltr

GEAREX EP-140 API GL-5



DESCRIPTION

Kizzexx Gear Oil SAE 140 API GL-5 are mixed with great mineral base oil, as well as some anti-wear and against froth added substance which has solid oxidation and frothing obstruction use in uncompromising activities tracked down in business armadas, manual transmission, axels and last drives.

MEETS OR EXCEEDS

API GL-5

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5 °C,gm/CC	ASTM D 4052	0.890
Viscosity @100 °C, cSt	ASTM D 445	23.00
Viscosity @40 °C, cSt	ASTM D 445	315
Viscosity Index	ASTM D 2270	91
Pour Point, °C	ASTM D 97	-9
Flash Point, °C	ASTM D 92	247
TBN, mgKOH/gm	ASTM D 892	0.0

PACKAGING SIZE

500ml, 1Ltr, 5Ltr, 10Ltr, 20Ltr
26Ltr, 55Ltr, 210Ltr

AXLEX 75W90 API GL-5



DESCRIPTION

Kizzexx Gear Oil SAE 75W-90 API GL-5 are mixed with great mineral base oil, as well as some anti-wear and against froth added substance which has solid oxidation and frothing obstruction use in uncompromising activities tracked down in business armadas, manual transmission, axels and last drives.

MEETS OR EXCEEDS

API GL-5

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5 °C,gm/CC	ASTM D 4052	0.835
Viscosity @100 °C, cSt	ASTM D 445	14.50
Viscosity @40 °C, cSt	ASTM D 445	94
Viscosity Index	ASTM D 2270	160
Pour Point, °C	ASTM D 97	-39
Flash Point, °C	ASTM D 92	220
TBN, mgKOH/gm	ASTM D 892	0.0

PACKAGING SIZE

500ml, 1Ltr, 5Ltr, 10Ltr, 20Ltr
26Ltr, 55Ltr, 210Ltr

AXLEX 80W90 API GL-5



DESCRIPTION

Kizzexx Gear Oil SAE 80W-90 API GL-5 is mixed with great mineral base oil, as well as some anti-wear and against froth added substance which has solid oxidation and frothing obstruction use in uncompromising activities tracked down in business armadas, manual transmission, axels and last drives.

MEETS OR EXCEEDS

API GL-5

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5 °C,gm/CC	ASTM D 4052	0.882
Viscosity @100 °C, cSt	ASTM D 445	15.50
Viscosity @40 °C, cSt	ASTM D 445	138.0
Viscosity Index	ASTM D 2270	116
Pour Point, °C	ASTM D 97	-24
Flash Point, °C	ASTM D 92	230
TBN, mgKOH/gm	ASTM D 892	0.0

PACKAGING SIZE

500ml, 1Ltr, 5Ltr, 10Ltr, 20Ltr
26Ltr, 55Ltr, 210Ltr

AUTOMOTIVE GEAR & TRANSMISSION OIL

GEAREX 85W140 API GL-5



DESCRIPTION

Kizzexx Gear Oil SAE 85W-140 API GL-5 are mixed with great mineral base oil, as well as some anti-wear and against froth added substance which has solid oxidation and frothing obstruction use in uncompromising activities tracked down in business armadas, manual transmission, axels and last drives.

MEETS OR EXCEEDS

API GL-5

SPECIFICATION


Appearance	VISUAL	C&B
Density @29.5°C, gm/CC	ASTM D 4052	0.890
Viscosity @100°C, cSt	ASTM D 445	25.6
Viscosity @40°C, cSt	ASTM D 445	356
Viscosity Index	ASTM D 2270	95
Pour Point, °C	ASTM D 97	-12
Flash Point, °C	ASTM D 92	245
TBN, mgKOH/gm	ASTM D 892	0.0

PACKAGING SIZE

500ml, 1Ltr, 5Ltr, 10Ltr, 20Ltr
26Ltr, 55Ltr, 210Ltr



OEM BUSINESS PARTNER



40FT CONTAINER LOAD UP TO 28 TON MAX



PRODUCT SIZE	UNIT	WEIGHT	QUANTITY	TOTAL WEIGHT
500ML CTN	25	13.86 KG	2020 CTN	27997 KG
1L CTN	20	19.70 KG	1421 CTN	27994 KG
1L CTN	12	11.75 KG	2382 CTN	27989 KG
3L CTN	6	18.24 KG	1323 CTN	24125 KG
3.5L CTN	6	20.09 KG	1323 CTN	26572 KG
5L CTN	4	19.5 KG	1248 CTN	24336 KG
7.5L PAIL	1	6.95 KG	3969 PAIL	27565 KG
10L PAIL	1	9.66 KG	2688 PAIL	25966 KG
20L PAIL	1	18.38 KG	1523 PAIL	27985 KG
20L DRUM	1	18.90 KG	1480 DRUM	27972 KG
26L DRUM	1	23.14 KG	1210 DRUM	27999 KG
50L DRUM	1	47.10 KG	560 DRUM	26320 KG
55L DRUM	1	51.50 KG	543 DRUM	27965 KG
208L BARREL	1	202 KG	138 BARREL	27876 KG
210L BARREL	1	203 KG	137 BARREL	27811 KG



HYDRAULIC OIL

HYDRAULIC OIL

HYDREX ISO 10W



DESCRIPTION

Kizzexx Hydraulic Oil ISO 10W is a high-performance anti-wear hydraulic oil specifically formulated from selected base oils and a proprietary additive system to provide well balanced performance in a range of applications. Manufactured from a high quality of virgin base oils combined with anti-wear additives and rust inhibitors.

MEETS OR EXCEEDS
DIN 51524 PART II

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5°C,gm/CC	ASTM D 4052	0.858
Viscosity @100°C, cSt	ASTM D 445	2.75
Viscosity @40°C, cSt	ASTM D 445	10.4
Viscosity Index	ASTM D 2270	105
Pour Point, °C	ASTM D 97	-15
Flash Point, °C	ASTM D 92	200
TBN, mgKOH/gm	ASTM D 892	0.0

PACKAGING SIZE

1Ltr, 5Ltr, 10Ltr, 20Ltr, 26Ltr
55Ltr, 210Ltr

HYDREX ISO 32



DESCRIPTION

Kizzexx Hydraulic Oil ISO 32 is a high-performance anti-wear hydraulic oil specifically formulated from selected base oils and a proprietary additive system to provide well balanced performance in a range of applications. Manufactured from a high quality of virgin base oils combined with anti-wear additives and rust inhibitors.

MEETS OR EXCEEDS
DIN 51524 PART II

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5°C,gm/CC	ASTM D 4052	0.868
Viscosity @100°C, cSt	ASTM D 445	5.38
Viscosity @40°C, cSt	ASTM D 445	32.40
Viscosity Index	ASTM D 2270	98
Pour Point, °C	ASTM D 97	-24
Flash Point, °C	ASTM D 92	232
TBN, mgKOH/gm	ASTM D 892	0.0

PACKAGING SIZE

1Ltr, 5Ltr, 10Ltr, 20Ltr, 26Ltr
55Ltr, 210Ltr

HYDREX ISO 46



DESCRIPTION

Kizzexx Hydraulic Oil ISO 46 is a high-performance anti-wear hydraulic oil specifically formulated from selected base oils and a proprietary additive system to provide well balanced performance in a range of applications. Manufactured from a high quality of virgin base oils combined with anti-wear additives and rust inhibitors.

MEETS OR EXCEEDS
DIN 51524 PART II

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5°C,gm/CC	ASTM D 4052	0.868
Viscosity @100°C, cSt	ASTM D 445	6.78
Viscosity @40°C, cSt	ASTM D 445	46.8
Viscosity Index	ASTM D 2270	98
Pour Point, °C	ASTM D 97	-30
Flash Point, °C	ASTM D 92	230
TBN, mgKOH/gm	ASTM D 892	0.0

PACKAGING SIZE

1Ltr, 5Ltr, 10Ltr, 20Ltr, 26Ltr
55Ltr, 210Ltr

HYDREX ISO 68



DESCRIPTION

Kizzexx Hydraulic Oil ISO 68 is a high-performance anti-wear hydraulic oil specifically formulated from selected base oils and a proprietary additive system to provide well balanced performance in a range of applications. Manufactured from a high quality of virgin base oils combined with anti-wear additives and rust inhibitors.

MEETS OR EXCEEDS
DIN 51524 PART II

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5°C,gm/CC	ASTM D 4052	0.875
Viscosity @100°C, cSt	ASTM D 445	8.72
Viscosity @40°C, cSt	ASTM D 445	68.90
Viscosity Index	ASTM D 2270	98
Pour Point, °C	ASTM D 97	-21
Flash Point, °C	ASTM D 92	240
TBN, mgKOH/gm	ASTM D 892	0.0

PACKAGING SIZE

1Ltr, 5Ltr, 10Ltr, 20Ltr, 26Ltr
55Ltr, 210Ltr

SPECIALIZED PRODUCT



SPECIAL AUTOMOTIVE PRODUCTS

TRANSMAX ATF(TQ) TYPE A



DESCRIPTION

Kizzexx Automatic Transmission Fluid TYPE A is a superior quality automatic transmission fluid meeting TYPE A specification. It is formulated to provide smooth shifting in the automatic and semi-automatic transmission due to high quality of base oil and the advance additives technology is used in the formulation.

MEETS OR EXCEEDS
ATF TYPE A

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5°C,gm/CC	ASTM D 4052	0.860
Viscosity @100°C, cSt	ASTM D 445	7.6
Viscosity @40°C, cSt	ASTM D 445	41.3
Viscosity Index	ASTM D 2270	155
Pour Point, °C	ASTM D 97	-28
Flash Point, °C	ASTM D 92	215
TBN, mgKOH/gm	ASTM D 892	0.0

PACKAGING SIZE

500ml, 1Ltr, 5Ltr, 20Ltr, 55Ltr, 210Ltr

BRAKEX DOT-3



DESCRIPTION

Kizzexx DOT 3 BRAKE FLUID is a high-quality synthetic brake and clutch fluid conforming to the DOT 3 specification and based on poly glycol type fluid that is a general standard used in worldwide automotive brake equipment. It is suitable for passenger cars, trucks and buses that require synthetic brake oil.

MEETS OR EXCEEDS
FMVSS 116 DOT-3

SPECIFICATION

Appearance	VISUAL	Transparent
Equilibrium reflex boiling point °C	FMVSS 116	205 max
Wet equilibrium RBP	FMVSS 116	140 min
Kinematic Viscosity @100°C	ASTM D 445	>1.5
PH	FMVSS 116	7.5 - 11.0
Specific Gravity 60°F	ASTM D 1298	1.07 - 1.15
Flash Point, °C	ASTM D 92	130min
Pour Point, °C	ASTM D 97	-

PACKAGING SIZE

100ml, 250ml, 500ml, 1Ltr, 5Ltr, 20Ltr, 55Ltr, 210Ltr

BRAKEX DOT-4



DESCRIPTION

Kizzexx DOT 4 BRAKE FLUID is a high-quality synthetic brake and clutch fluid conforming to the DOT 4 specification and based on poly glycol type fluid that is a general standard used in worldwide automotive brake equipment. It is suitable for passenger cars, trucks and buses that require synthetic brake oil.

MEETS OR EXCEEDS
FMVSS 116 DOT-4

SPECIFICATION

Appearance	VISUAL	Transparent
Equilibrium reflex boiling point °C	FMVSS 116	235 max
Wet equilibrium RBP	FMVSS 116	150 min
Kinematic Viscosity @100°C	ASTM D 445	>1.5
PH	FMVSS 116	7.5 - 11.0
Specific Gravity 60°F	ASTM D 1298	1.07 - 1.15
Flash Point, °C	ASTM D 92	121min
Pour Point, °C	ASTM D 97	-

PACKAGING SIZE

100ml, 250ml, 500ml, 1Ltr, 5Ltr, 20Ltr, 55Ltr, 210Ltr

FORKEX SAE 10W



DESCRIPTION

Kizzexx Fork Oil 10W is an advanced mineral-based suspension fluid designed to provide the optimum damping performance in all on and off-road suspensions. Its highly refined base stock and naturally high viscosity index will provide superior anti-fade damping performance over a wide temperature range.

MEETS OR EXCEEDS
-

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5°C,gm/CC	ASTM D 4052	0.880
Viscosity @100°C, cSt	ASTM D 445	6.30
Viscosity @40°C, cSt	ASTM D 445	32
Viscosity Index	ASTM D 2270	150
Pour Point, °C	ASTM D 97	-39
Flash Point, °C	ASTM D 92	210
TBN, mgKOH/gm	ASTM D 892	0.0

PACKAGING SIZE

175ml, 350ml, 1Ltr, 5Ltr, 20Ltr, 55Ltr, 210Ltr



INDUSTRIAL & TEXTILE OIL

INDUSTRIAL & TEXTILE OIL

GEAREX EP-100 API GL-5



DESCRIPTION

Kizzexx Gear EP-100 are high performance extreme pressure oils designed for lubrication of heavy-duty industrial gears. These are formulated with high quality mineral base oils along with specially selected additive technology to provide excellent load carrying capacity even under extreme conditions including shock loading.

MEETS OR EXCEEDS

API GL-5

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5°C,gm/CC	ASTM D 4052	0.890
Viscosity @100°C, cSt	ASTM D 445	17.00
Viscosity @40°C, cSt	ASTM D 445	101.2
Viscosity Index	ASTM D 2270	>95
Pour Point, °C	ASTM D 97	-18
Flash Point, °C	ASTM D 92	234
Copper Corrosion @100°C	ASTM D 130	1b

PACKAGING SIZE

5Ltr, 10Ltr, 20Ltr, 26Ltr
55Ltr, 210Ltr

GEAREX EP-150 API GL-5



DESCRIPTION

Kizzexx Gear EP-150 are high performance extreme pressure oils designed for lubrication of heavy-duty industrial gears. These are formulated with high quality mineral base oils along with specially selected additive technology to provide excellent load carrying capacity even under extreme conditions including shock loading.

MEETS OR EXCEEDS

API GL-5

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5°C,gm/CC	ASTM D 4052	0.893
Viscosity @100°C, cSt	ASTM D 445	20.02
Viscosity @40°C, cSt	ASTM D 445	145.20
Viscosity Index	ASTM D 2270	>95
Pour Point, °C	ASTM D 97	-18
Flash Point, °C	ASTM D 92	234
Copper Corrosion @100°C	ASTM D 892	1b

PACKAGING SIZE

5Ltr, 10Ltr, 20Ltr, 26Ltr
55Ltr, 210Ltr

GEAREX EP-220 API GL-5



DESCRIPTION

Kizzexx Gear EP-220 are high performance extreme pressure oils designed for lubrication of heavy-duty industrial gears. These are formulated with high quality mineral base oils along with specially selected additive technology to provide excellent load carrying capacity even under extreme conditions including shock loading.

MEETS OR EXCEEDS

API GL-5

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5°C,gm/CC	ASTM D 4052	0.896
Viscosity @100°C, cSt	ASTM D 445	22.08
Viscosity @40°C, cSt	ASTM D 445	242
Viscosity Index	ASTM D 2270	>95
Pour Point, °C	ASTM D 97	-18
Flash Point, °C	ASTM D 92	234
Copper Corrosion @100°C	ASTM D 892	1b

PACKAGING SIZE

5Ltr, 10Ltr, 20Ltr, 26Ltr
55Ltr, 210Ltr

GEAREX EP-320 API GL-5



DESCRIPTION

Kizzexx Gear EP-320 are high performance extreme pressure oils designed for lubrication of heavy-duty industrial gears. These are formulated with high quality mineral base oils along with specially selected additive technology to provide excellent load carrying capacity even under extreme conditions including shock loading.

MEETS OR EXCEEDS

API GL-5

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5°C,gm/CC	ASTM D 4052	0.899
Viscosity @100°C, cSt	ASTM D 445	24.02
Viscosity @40°C, cSt	ASTM D 445	322
Viscosity Index	ASTM D 2270	>95
Pour Point, °C	ASTM D 97	-18
Flash Point, °C	ASTM D 92	234
Copper Corrosion @100°C	ASTM D 892	1b

PACKAGING SIZE

5Ltr, 10Ltr, 20Ltr, 26Ltr
55Ltr, 210Ltr

INDUSTRIAL & TEXTILE OIL

GEAREX EP-460 API GL-5



DESCRIPTION

Kizzexx Gear EP-460 are high performance extreme pressure oils designed for lubrication of heavy-duty industrial gears. These are formulated with high quality mineral base oils along with specially selected additive technology to provide excellent load carrying capacity even under extreme conditions including shock loading.

MEETS OR EXCEEDS

API GL-5

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5 °C, gm/CC	ASTM D 4052	0.899
Viscosity @100 °C, cSt	ASTM D 445	27.50
Viscosity @40 °C, cSt	ASTM D 445	457
Viscosity Index	ASTM D 2270	>95
Pour Point, °C	ASTM D 97	-18
Flash Point, °C	ASTM D 92	234
Copper Corrosion @100 °C	ASTM D 130	1b

PACKAGING SIZE

5Ltr, 10Ltr, 20Ltr, 26Ltr
55Ltr, 210Ltr

GEAREX EP-680 API GL-5



DESCRIPTION

Kizzexx Gear EP-680 are high performance extreme pressure oils designed for lubrication of heavy-duty industrial gears. These are formulated with high quality mineral base oils along with specially selected additive technology to provide excellent load carrying capacity even under extreme conditions including shock loading.

MEETS OR EXCEEDS

API GL-5

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5 °C, gm/CC	ASTM D 4052	0.899
Viscosity @100 °C, cSt	ASTM D 445	29.50
Viscosity @40 °C, cSt	ASTM D 445	678
Viscosity Index	ASTM D 2270	>95
Pour Point, °C	ASTM D 97	-18
Flash Point, °C	ASTM D 92	234
Copper Corrosion @100 °C	ASTM D 892	1b

PACKAGING SIZE

5Ltr, 10Ltr, 20Ltr, 26Ltr
55Ltr, 210Ltr

KIZZEXX SPINDLE OIL ISO-10



DESCRIPTION

Kizzexx Spindle Oil 10 is based upon highly mineral base stocks enhanced with rust and oxidation inhibitors and formulated especially for the lubrication of high speed and precision machine tool spindle bearings. It has been specially formulated to provide outstanding protection against rust and oxidation.

MEETS OR EXCEEDS

ISO 10

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5 °C, gm/CC	ASTM D 4052	0.868
Viscosity @100 °C, cSt	ASTM D 445	2.6
Viscosity @40 °C, cSt	ASTM D 445	10.00
Viscosity Index	ASTM D 2270	104
Pour Point, °C	ASTM D 97	-22
Flash Point, °C	ASTM D 92	226
Copper Corrosion @100 °C	ASTM D 892	-

PACKAGING SIZE

5Ltr, 10Ltr, 20Ltr, 26Ltr
55Ltr, 210Ltr

KIZZEXX WARPING OIL



DESCRIPTION

Kizzexx Warping Oil has been specially designed for warping application of textile yarn. Weaving of textile is a process of interlacing warps with wefts. In a fabric, longitudinal yarns are called warps, and lateral or cross yarns are called wefts. In warping application, warp yarns are arranged parallel to each other.

MEETS OR EXCEEDS

-

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5 °C, gm/CC	ASTM D 4052	0.848
Viscosity @100 °C, cSt	ASTM D 445	5.2
Viscosity @40 °C, cSt	ASTM D 445	30.16
Viscosity Index	ASTM D 2270	104
Pour Point, °C	ASTM D 97	-26
Flash Point, °C	ASTM D 92	226
Copper Corrosion @100 °C	ASTM D 892	-

PACKAGING SIZE

20Ltr, 55Ltr, 210Ltr

INDUSTRIAL & TEXTILE OIL

KIZZEXX LOOMS OIL-460 API GL-5



DESCRIPTION

Kizzexx Looms-460 are high performance extreme pressure oils designed for lubrication of heavy-duty industrial gears. These are formulated with high quality mineral base oils along with specially selected additive technology to provide excellent load carrying capacity even under extreme conditions including shock loading.

MEETS OR EXCEEDS

API GL-5

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5°C,gm/CC	ASTM D 4052	0.899
Viscosity @100°C, cSt	ASTM D 445	27.50
Viscosity @40°C, cSt	ASTM D 445	457
Viscosity Index	ASTM D 2270	>95
Pour Point, °C	ASTM D 97	-18
Flash Point, °C	ASTM D 92	234
Copper Corrosion @100°C	ASTM D 130	1b

PACKAGING SIZE

5Ltr, 10Ltr, 20Ltr, 26Ltr
55Ltr, 210Ltr

KIZZEXX COMPRESSOR OIL-150



DESCRIPTION

Kizzexx Compressor Oil 150 are high quality, high performance mineral oils developed for reciprocating air compressors. They are formulated from highly refined, high viscosity index base stocks and high-performance additives with ashless chemistry. Reciprocating compressors operate at high temperatures and pressures.

MEETS OR EXCEEDS

ISO / DP 6521

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5°C,gm/CC	ASTM D 4052	0.893
Viscosity @100°C, cSt	ASTM D 445	17.02
Viscosity @40°C, cSt	ASTM D 445	145.2
Viscosity Index	ASTM D 2270	105
Pour Point, °C	ASTM D 97	-18
Flash Point, °C	ASTM D 92	234
Copper Corrosion @100°C	ASTM D 892	1b

PACKAGING SIZE

5Ltr, 10Ltr, 20Ltr, 26Ltr
55Ltr, 210Ltr

KIZZEXX COMPRESSOR OIL-220



DESCRIPTION

Kizzexx Compressor Oil 220 are high quality, high performance mineral oils developed for reciprocating air compressors. They are formulated from highly refined, high viscosity index base stocks and high-performance additives with ashless chemistry. Reciprocating compressors operate at high temperatures and pressures.

MEETS OR EXCEEDS

ISO 10

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5°C,gm/CC	ASTM D 4052	0.896
Viscosity @100°C, cSt	ASTM D 445	22.08
Viscosity @40°C, cSt	ASTM D 445	242
Viscosity Index	ASTM D 2270	105
Pour Point, °C	ASTM D 97	-18
Flash Point, °C	ASTM D 92	234
Copper Corrosion @100°C	ASTM D 892	1b

PACKAGING SIZE

5Ltr, 10Ltr, 20Ltr, 26Ltr
55Ltr, 210Ltr

KIZZEXX 20W40 INDUSTRIAL OIL



DESCRIPTION

Waxy 20W40 Industrial oil is a high quality industrial engine oil blended with superior quality high viscosity index base oil and well balanced group of additives to provide high detergency, dispersancy and anti-oxidation characteristics. This oil is formulated to perform under the most stringent operating conditions of industrial equipment.

MEETS OR EXCEEDS

-

SPECIFICATION

Appearance	VISUAL	C&B
Density @29.5°C,gm/CC	ASTM D 4052	0.852
Viscosity @100°C, cSt	ASTM D 445	14.16
Viscosity @40°C, cSt	ASTM D 445	110.90
Viscosity Index	ASTM D 2270	120
Pour Point, °C	ASTM D 97	-22
Flash Point, °C	ASTM D 92	231
TBN, mgKOH/gm	ASTM D 892	5.6

PACKAGING SIZE

5Ltr, 10Ltr, 20Ltr, 26Ltr
55Ltr, 210Ltr

A close-up photograph showing a person's hand applying a thick, yellow, semi-solid grease to a metal bearing. The bearing is a complex mechanical part with a central hole and a textured inner surface. The grease is being applied in a thick, stringy consistency. The background is dark and out of focus, suggesting an industrial or automotive setting. The entire image is framed by a white border with a slight shadow effect.

**AUTOMOTIVE &
INDUSTRIAL GREASE**

AUTOMOTIVE & INDUSTRIAL GREASE

KIZZEXX EP-2 GREASE



DESCRIPTION

Kizzexx EP-2 is a general-purpose lithium grease formulated to provide protection against wear, corrosion and water washout. Available as an NLGI 2 grade with a base oil to address a variety of both industrial and commercial vehicle applications. EP-2 is recommended for most types of industrial applications.

MEETS OR EXCEEDS
NLGI-2 | LITHIUM

SPECIFICATION

NLGI Grade	-	2
Soap Type	-	LITHIUM COMPLEX
Viscosity Of Oil @100 °C, cSt	ASTM D 445	18
Viscosity Of Oil @40 °C, cSt	ASTM D 445	105
Worked Penetration @25 °C	ASTM D 217	275
Drop Point, °C	ASTM D 2265	195
Water Washout @79 °C	ASTM D 1264	<10
Copper Stripe Corrosion	ASTM D 4048	1b

PACKAGING SIZE

1Kg, 2Kg, 5Kg, 10Kg, 18Kg, 180Kg

KIZZEXX EP-0 GREASE



DESCRIPTION

Waxy EP-0 grease is multipurpose extreme pressure lithium soap-based grease for use in a wide range of heavy duty on-road trucking and automotive applications as well as varied industrial applications. These are manufactured from high quality base oils and performance additives to provide excellent wear protection.

MEETS OR EXCEEDS
NLGI-0 | LITHIUM

SPECIFICATION

NLGI Grade	-	0
Soap Type	-	LITHIUM
Viscosity Of Oil @100 °C, cSt	ASTM D 445	32
Viscosity Of Oil @40 °C, cSt	ASTM D 445	180
Worked Penetration @25 °C	ASTM D 217	370
Drop Point, °C	ASTM D 2265	180
Water Washout @79 °C	ASTM D 1264	<10
Copper Stripe Corrosion	ASTM D 4048	1b

PACKAGING SIZE

1Kg, 2Kg, 5Kg, 10Kg, 18Kg, 180Kg

KIZZEXX EP-00 GREASE



DESCRIPTION

Waxy EP-00 grease is multipurpose extreme pressure lithium soap-based grease for use in a wide range of heavy duty on-road trucking and automotive applications and industrial applications. These are manufactured from high quality base oils and performance additives to provide excellent wear protection.

MEETS OR EXCEEDS
NLGI-00 | LITHIUM

SPECIFICATION

NLGI Grade	-	00
Soap Type	-	LITHIUM
Viscosity Of Oil @100 °C, cSt	ASTM D 445	32
Viscosity Of Oil @40 °C, cSt	ASTM D 445	180
Worked Penetration @25 °C	ASTM D 217	415
Drop Point, °C	ASTM D 2265	170
Water Washout @79 °C	ASTM D 1264	<10
Copper Stripe Corrosion	ASTM D 4048	1b

PACKAGING SIZE

1Kg, 2Kg, 5Kg, 10Kg, 18Kg, 180Kg

KIZZEXX EP-000 GREASE



DESCRIPTION

Waxy EP-000 grease is multipurpose extreme pressure lithium soap-based grease for use in a wide range of heavy duty on-road trucking and automotive applications and industrial applications. These are manufactured from high quality base oils and performance additives to provide excellent wear protection.

MEETS OR EXCEEDS
NLGI-000 | LITHIUM

SPECIFICATION

NLGI Grade	-	000
Soap Type	-	LITHIUM
Viscosity Of Oil @100 °C, cSt	ASTM D 445	32
Viscosity Of Oil @40 °C, cSt	ASTM D 445	180
Worked Penetration @25 °C	ASTM D 217	455
Drop Point, °C	ASTM D 2265	160
Water Washout @79 °C	ASTM D 1264	<10
Copper Stripe Corrosion	ASTM D 4048	1b

PACKAGING SIZE

1Kg, 2Kg, 5Kg, 10Kg, 18Kg, 180Kg

AUTOMOTIVE & INDUSTRIAL GREASE

KIZZEXX AP-3 GREASE



DESCRIPTION

Kizzexx AP-3 Grease is all purpose lithium soap base grease having excellent shear stability, high load carrying properties & prevent welding & seizure of moving parts under shock loading conditions. These greases are recommended for industrial & automotive, earth moving equipment, gear couplings, electric motors etc.

MEETS OR EXCEEDS

NLGI-3 | LITHIUM

SPECIFICATION

NLGI Grade	-	3
Soap Type	-	LITHIUM
Viscosity Of Oil @100 °C, cSt	ASTM D 445	32
Viscosity Of Oil @40 °C, cSt	ASTM D 445	180
Worked Penetration @25 °C	ASTM D 217	455
Drop Point, °C	ASTM D 2265	160
Water Washout @79 °C	ASTM D 1264	<10
Copper Stripe Corrosion	ASTM D 4048	1b

PACKAGING SIZE

250gm, 500gm, 1Kg, 2Kg, 5Kg
10Kg, 18Kg, 180Kg

KIZZEXX MP-3 GREASE



DESCRIPTION

Kizzexx MP-3 Grease is a premium quality calcium based multipurpose grease manufactured from superior quality base oils. This grease is fortified with a well-balanced additive chemistry comprising of antioxidant, anti-wear and anti-rust additives making it suitable for a wide range of general-purpose applications.

MEETS OR EXCEEDS

NLGI-3 | CALCIUM

SPECIFICATION

Appearance	-	Light Yellow
Soap Type	-	CALCIUM
Viscosity Of Oil @100 °C, cSt	ASTM D 445	18
Viscosity Of Oil @40 °C, cSt	ASTM D 445	62
Worked Penetration @25 °C	ASTM D 217	237
Drop Point, °C	ASTM D 2265	106
Water Washout @79 °C	ASTM D 1264	<5
Copper Stripe Corrosion	ASTM D 4048	Negative

PACKAGING SIZE

250gm, 500gm, 1Kg, 2Kg, 5Kg
10Kg, 18Kg, 180Kg

KIZZEXX GEL GREASE



DESCRIPTION

Kizzexx Gel Grease is a premium quality calcium based shiny gel type grease formulated using premium quality base oil, special calcium-based thickener technology and advanced additive package. This grease offers exceptional shear stability and load carrying capacity, making it suitable for heavily loaded bearings.

MEETS OR EXCEEDS

NLGI-3 | CALCIUM

SPECIFICATION

NLGI Grade	-	3
Soap Type	-	CALCIUM
Viscosity Of Oil @100 °C, cSt	ASTM D 445	18
Viscosity Of Oil @40 °C, cSt	ASTM D 445	62
Worked Penetration @25 °C	ASTM D 217	235
Drop Point, °C	ASTM D 2265	106
Water Washout @79 °C	ASTM D 1264	<5
Copper Stripe Corrosion	ASTM D 4048	Negative

PACKAGING SIZE

250gm, 500gm, 1Kg, 2Kg, 5Kg
10Kg, 18Kg, 180Kg

KIZZEXX RED GEL GREASE



DESCRIPTION

Kizzexx Red Gel Grease is a premium quality calcium based shiny gel type grease formulated using premium quality base oil, special calcium-based thickener technology and advanced additive package. This grease offers exceptional shear stability and load carrying capacity, making it suitable for heavily loaded bearings.

MEETS OR EXCEEDS

NLGI-3 | CALCIUM

SPECIFICATION

NLGI Grade	-	3
Soap Type	-	CALCIUM
Viscosity Of Oil @100 °C, cSt	ASTM D 445	18
Viscosity Of Oil @40 °C, cSt	ASTM D 445	62
Worked Penetration @25 °C	ASTM D 217	235
Drop Point, °C	ASTM D 2265	106
Water Washout @79 °C	ASTM D 1264	<5
Copper Stripe Corrosion	ASTM D 4048	Negative

PACKAGING SIZE

250gm, 500gm, 1Kg, 2Kg, 5Kg
10Kg, 18Kg, 180Kg

AUTOMOTIVE & INDUSTRIAL GREASE

KIZZEXX TITANIUM-3 GREASE



DESCRIPTION

Kizzexx TITANIUM-3 GREASE is high performance lithium complex grease designed for lubrication of bearings of most automotive and industrial equipment. This grease is based on high quality base fluid and superior lithium complex soap thickener fortified with excellent anti oxidation, anti-rust and anti-wear additive systems.

MEETS OR EXCEEDS

NLGI-3 | LITHIUM

SPECIFICATION

NLGI Grade	-	3
Soap Type	-	LITHIUM COMPLEX
Viscosity Of Oil @100 °C, cSt	ASTM D 445	18
Viscosity Of Oil @40 °C, cSt	ASTM D 445	220
Worked Penetration @25 °C	ASTM D 217	236
Drop Point, °C	ASTM D 2265	>265
Water Washout @79 °C	ASTM D 1264	<5
Copper Stripe Corrosion	ASTM D 4048	1a

PACKAGING SIZE

250gm, 500gm, 1Kg, 2Kg, 5Kg
10Kg, 18Kg, 180Kg

KIZZEXX HIGH TEMPERATURE GREASE



DESCRIPTION

Kizzexx High Temperature Grease is a high performance, multipurpose lithium complex grease developed using an optimized combination of high-quality mineral oil, thickener technology and a specially selected additive system enabling reliable performance across a wide range of temperatures and speeds.

MEETS OR EXCEEDS

NLGI-2 | LITHIUM

SPECIFICATION

NLGI Grade	-	2
Soap Type	-	CLAY
Viscosity Of Oil @100 °C, cSt	ASTM D 445	40.90
Viscosity Of Oil @40 °C, cSt	ASTM D 445	500
Worked Penetration @25 °C	ASTM D 217	275
Drop Point, °C	ASTM D 2265	>280
Water Washout @79 °C	ASTM D 1264	<5
Copper Stripe Corrosion	ASTM D 4048	1a

PACKAGING SIZE

250gm, 500gm, 1Kg, 2Kg, 5Kg
10Kg, 18Kg, 180Kg

KIZZEXX CHASSIS GREASE



DESCRIPTION

Kizzexx Chassis Grease is premium quality sodium based automotive grease manufactured from superior quality base stocks and specially selected additives. Chassis grease is having moderately high drop points, resistance to oxidation, good thermal and structural stability and Also provides protection against rust.

MEETS OR EXCEEDS

SODIUM GREASE

SPECIFICATION

Appearance	-	Greenish Brown
Soap Type	-	SODIUM
Unworked Penetration @25 °C	0.1 mm units	290-320
Titled Leakage, Max	-	5
Worked Penetration @25 °C	ASTM D 217	290-320
Drop Point, °C	ASTM D 2265	95
Water Washout % @79 °C	-	0.1
Copper Stripe Corrosion	ASTM D 4048	1b

PACKAGING SIZE

250gm, 500gm, 1Kg, 2Kg, 5Kg
10Kg, 18Kg, 180Kg

KIZZEXX WHEEL BEARING GREASE



DESCRIPTION

Kizzexx Wheel Bearing Grease is heavy duty sodium soap automotive grease formulated with tailor-made fats mineral oil and selected additives to ensure good stability and load bearing capacity under the most severe conditions. wheel bearing Grease does not melt even at extended hauling, where other greases are likely to flow out.

MEETS OR EXCEEDS

SODIUM GREASE

SPECIFICATION

Appearance	-	Dark Greenish Brown
Soap Type	-	SODIUM
Unworked Penetration @25 °C	0.1 mm units	235-255
Titled Leakage, Max	-	5
Worked Penetration @25 °C	ASTM D 217	235-255
Drop Point, °C	ASTM D 2265	178
Water Washout % @79 °C	-	0.1
Copper Stripe Corrosion	ASTM D 4048	1b

PACKAGING SIZE

250gm, 500gm, 1Kg, 2Kg, 5Kg
10Kg, 18Kg, 180Kg



 **KIZZEXX INDUSTRIES PVT LTD**

Plot No: 53, Shiv Bhakti Industries, Kadodara To Palsana
Highway, Karan, Village Sanki, Chalthan,
Surat-395305, Gujarat-INDIA.