

## Product Description & Application

Kizzexx 20W40 API SJ/JASO MA is a high-performance engine oil, especially designed for modern motorcycles. Though developed for latest technology, It provides good protection for old technology engines too, while aligning with motorcycle engine technology development trends meets major OEMs. Instant engine protection from Heat-activated anti-wear molecule protects engine right from its start to the high temperature conditions caused by long, continuous driving. Under high RPM and high temperature circumstances, It has the best frictional properties for maximum power transfer, effortless shifting, and proper wet clutch protection.

## Features & Benefits

- Provide maximum protection for all vehicle.
- Low emission engines and high-performance vehicles.
- Protection against engine wear and excellent low temperature.
- Special cleaning agents and dispersants help prevent deposit formation.

## Meets Or Exceeds

- API SJ
- JASO MA2

## Typical Characteristics

TEST	METHOD	RESULT
Appearance	VISUAL	C&B
Density @29.5°C, gm/CC	ASTM D 4052	0.852
Viscosity @100°C, cSt	ASTM D 445	14.16
Viscosity @40°C, cSt	ASTM D 445	110.90
Viscosity Index	ASTM D 2270	120
Pour Point, °C	ASTM D 97	-22
Flash Point, °C	ASTM D 92	231
TBN, mgKOH/gm	ASTM D 892	5.6