

Product Description & Application

Kizzexx Full Synthetic Engine Oil API SP SAE 5W30 is an advanced fully Synthetic motor oil designed to keep your engine running like new by providing exceptional wear protection, cleaning power and overall performance. A fuel economy, universal motor oil, developed according to the most recent technology, based on specially selected synthetic base oils to which advanced additives are added to obtain the below features. It gives great wear control to safeguard the motor in various atmospheric conditions and unforgiving applications, protecting the motor in cold climate are up and warm climate conditions.

Features & Benefits

- Provides excellent overall performance.
- Enhanced frictional properties that aids fuel economy.
- Provides exceptional cleaning power for dirty engines.
- Excellent low temperature capabilities for rapid engine protection at start-up.

Meets Or Exceeds

- API SP
- ILSAC GF-6A

Typical Characteristics

TEST	METHOD	RESULT
Appearance	VISUAL	C&B
Density @29.5°C, gm/CC	ASTM D 4052	0.835
Viscosity @100°C, cSt	ASTM D 445	11.50
Viscosity @40°C, cSt	ASTM D 445	68.20
Viscosity Index	ASTM D 2270	164
Pour Point, °C	ASTM D 97	-39
Flash Point, °C	ASTM D 92	220
TBN, mgKOH/gm	ASTM D 892	7.1