

Product Description & Application

Kizzexx Compressor Oil 150 are high quality, high performance mineral oils developed for reciprocating air compressors. They are formulated from highly refined, high viscosity index base stocks and high-performance additives with ashless chemistry. Reciprocating compressors operate at high temperatures and pressures. The lubricant creates a strong film in order to avoid surface wear. These oils have exceptional resistance to oxidation and thermal degradation. The thermal stability and oxidation resistance of these fluids can help maintain cleaner compressors, thereby enabling longer running periods between scheduled maintenance and oil changes.

Features & Benefits

- Outstanding oxidation stability provides resistance to the effects of oxidizing agents.
- Good thermal stability provides good resistance to thermal break down and capability to work under varied ambient temperatures to offer optimum life and performance.
- Rapid air release and resistance to foaming.

Meets Or Exceeds

- DIN 51506 – VDL
- ISO/ DP 6521

Typical Characteristics

TEST	METHOD	RESULT
Appearance	VISUAL	C&B
Density @29.5°C, gm/CC	ASTM D 4052	0.875
Viscosity @100°C, cSt	ASTM D 445	8.72
Viscosity @40°C, cSt	ASTM D 445	68.9
Viscosity Index	ASTM D 2270	98
Pour Point, °C	ASTM D 97	-21
Flash Point, °C	ASTM D 92	240
Copper Corrosion @100°C	ASTM D 130	0.0