

Product Description & Application

Kizzexx DOT 3 BRAKE FLUID is a high-quality synthetic brake and clutch fluid conforming to the DOT 3 specification and based on poly glycol type fluid that is a general standard used in worldwide automotive brake equipment. It is suitable for passenger cars, trucks and buses that require synthetic brake oil. Brake fluid is a type of hydraulic fluid used in hydraulic brake and clutch applications in automobiles, motorcycles, light trucks and some bicycles. It is used to transfer force into pressure. It's recommended for complete fluid replacement and "top up" in most cars and light trucks.

Features & Benefits

- PUnique Low Moisture Activity (LMA).
- Recommended for all anti-lock braking systems (ABS).
- Hydraulic drum and disc braking systems and hydraulic clutches requiring DOT 3 fluids.
- Provides superior fluidity at low temperatures for optimum braking response.

Meets Or Exceeds

- FMVSS 116 DOT 3
- SAE J1703

Typical Characteristics

TEST	METHOD	RESULT
Appearance	VISUAL	Transparent
Equilibrium reflux boiling point°C	FMVSS 116	205 max
Wet equilibrium RBP	FMVSS 116	140 min
Kinematic Viscosity@ 100°C	ASTM D 445	>1.5
PH	FMVSS 116	7.5 - 11.0
Specific Gravity 60 °F	ASTM D 1298	1.07 - 1.15
Flash Point, °C	ASTM D 92	130 min
Pour Point, °C	ASTM D 97	-