

Product Description & Application

Kizzexx 15W-50 API SN / JASO MA2 is a synthetic blend formulated specifically for new generation higher CC four stroke motorcycles ideal for daily commute or recreational riding. It offers superior wear protection, excellent oxidation resistance, and improved oil film that keeps the engine running efficiently even under highly stressed engine operating conditions. The dedicated formulation ensures consistent power delivery to the motorcycle over extended periods. Under high RPM and high temperature circumstances, It has the best frictional properties for maximum power transfer, effortless shifting, and proper wet clutch protection.

Features & Benefits

- Provide maximum protection for all vehicles.
- Low emission engines and high-performance vehicles.
- Protection against engine wear and excellent low temperature.
- Special cleaning agents and dispersants help prevent deposit formation.

Meets Or Exceeds

- API SN
- JASO MA2

Typical Characteristics

| TEST | METHOD | RESULT |
|------------------------|-------------|--------|
| Appearance | VISUAL | C&B |
| Density @29.5°C, gm/CC | ASTM D 4052 | 0.860 |
| Viscosity @100°C, cSt | ASTM D 445 | 18.90 |
| Viscosity @40°C, cSt | ASTM D 445 | 155.10 |
| Viscosity Index | ASTM D 2270 | 138 |
| Pour Point, °C | ASTM D 97 | -28 |
| Flash Point, °C | ASTM D 92 | 244 |
| TBN, mgKOH/gm | ASTM D 892 | 6.2 |